

FlamSafe Secure Flammable Liquid Storage Box

FLAMSAFE®



Sizes Available

Floor-Standing:

380Hx360Wx370Dmm
555Hx460Wx420Dmm
555Hx660Wx420Dmm
555Hx890Wx420Dmm
555Hx1190Wx420Dmm



Storage & Sump Capacity:

Product code: SFS383637ZRX - FlamSafe® 1 - 380Hx360Wx370Dmm -
2x 5L Cans, sump capacity - 16 litres

Product code: SFS554642ZRX - FlamSafe® 2 - 555Hx460Wx420Dmm -
2x 20L Cans, sump capacity - 40 litre

Product code: SFS556642ZRX - FlamSafe® 3 - 555Hx660Wx420Dmm -
3x 20L Cans, sump capacity - 75 litres

Product code: SFS558942ZRX - FlamSafe® 4 - 555Hx890Wx420Dmm -
4x 20L Cans, sump capacity - 80 litres

Product code: SFS551142ZRX - FlamSafe® 5 - 555Hx1190Wx420Dmm -
6x 20L Cans, sump capacity - 100 litres

48 HOUR
DELIVERY



Product Weight:

Product code:

FlamSafe 1® - 12.45KG - 380H x 360W x 370Dmm

FlamSafe 2® - 18.65KG - 555H x 460W x 420Dmm

FlamSafe 3® - 24.80KG - 555H x 660W x 420Dmm

FlamSafe 4® - 30.20KG - 555H x 890W x 420Dmm

FlamSafe 5® - 37.45KG - 555H x 1190W x 420Dmm

FlamSafe Secure Flammable Liquid Storage Box



Paint Finish

A three-stage pre-treatment and phosphate coating are applied.

Carcass and doors are powder-coated with one coat of epoxy polyester full gloss powder, stoved at 180deg, including our germ guard anti-bacterial compound.

The product is powder-coated - Red RAL 3003.



Cleaning & Maintenance

Clean paint work periodically with warm soapy water or foaming cleaner.

Clean toggle lock sparingly as required with a light oil (3in1 or similar).



Security Box Construction

Construction:

- Delivered as an assembled unit, with the plastic handles to be fixed to the unit. These are bolted to the unit with an allen key.
- Warning/hazardous labels supplied.
- Reaction to Fire Classification EN 13501-1 – supporting documents are available from our sales or marketing team.
- Material: 1.5mm mild steel.
- Internal ventilation.
- Supplied with toggle latch lock (padlock not supplied - diameter loop is 7.2mm, recommended 6mm shackle padlock.
- Site security box can be bolted to the floor or used as a floor-standing unit. 1 bolt hole only for FlamSafe® 1, the other units have 2 bolt holes.



48 Hour Delivery

All sizes are available on our 48 hour delivery service.